

## Declaration of performance

No. 001DoP-3mm-130701

- Unique identification code of the product type:** Dry-pressed ceramic tiles with water absorption  $E_b \leq 0,5\%$ ; nominal thickness 3 mm.
- Intended use:** For internal and external walls.
- Name or registered trade mark, and contact address of the manufacturer:** Laminam S.p.A. via Ghiarola Nuova, 258 – 41042 Fiorano Modenese (MO) – Italy.
- System of assessment and verification of constancy of performance (AVCP):** System 4.
- Name and identification number of notified laboratory, if relevant:** not applicable.
- Declared performance:**

<u>Essential characteristics</u>	<u>Performance</u>	<u>Harmonized technical specification</u>
Name	Laminam 3	EN 14411:2012
Reaction to fire	A1	
Release of dangerous substance, for:		
– Cadmium	NPD	
– Lead	NPD	
Bond strength/adhesion, for:		
Cementitious adhesive, type C2S1/C2S2	1 N/mm <sup>2</sup>	
Thermal shock resistance	Pass	
Durability for:		
– Internal use	Pass	
– External use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Marina Fiore, QSE Manager

Fiorano Modenese, 01<sup>st</sup> July 2013

Signature

mf / AS